

Wind Vane Thies Compact POT

Potentiometric wind direction transmitter



Description

- Potentiometric wind direction transmitter
- Full range 0 ... 360°
- High quality potentiometer 0 ... 2 kΩ

Measurement principle

With the help of a potentiometer the physical property is converted into an analogue resistor output signal. At zero the transducer has to pass the „north transition“ between the margins of zero and 2 kΩ.

Wind direction signal conditioning and data processing in all Ammonit data acquisition systems carefully pays attention to this speciality.

The wind vane can be equipped with an electronically regulated heating system in order to prevent ice from the bearings. To use this heating the connection cable must have additional cores and you should provide a sufficient power supply (mains connection).

Specifications

Characteristic	Description / Value
Measuring range	0 ... 360°
Measuring accuracy	± 2°
Survival speed	max. 80 m/s, 30 min
Ambient temperature	-40 ... +70 °C
Measurement principle	Potentiometer 2 kΩ
Resolution	0.5°

Characteristic	Description / Value
Starting threshold	≤ 1 m/s according to ASTM-Standards D5366-96 ≤ 0.4 m/s according to VDI-Standard 3786 Part 2
Delay distance	< 2.5 m acc. ASTM D 5366-96
Electrical supply Potentiometer	Voltage U_s : 0 ... 24 VDC Important: The supply voltage of the potentiometer must show a current limitation of max. 1 mA. An additional protective resistance is strongly recommended. Resistor R_v : 15 k Ω @ supply voltage: 12 ... 15 V
Heating	24 VDC/AC (Power consumption: max. 20 W)
Connection	7-pole plug
Mast fixture	Mounted on a steel tube with an inner thread of PG21 or mounted on a traverse with a drill of 29 mm
Material	Aluminum, stainless steel and plastic (Housing and wind vane)
Type of ball bearings	Metallic ball bearings
Protection	IP 55
Weight	approx. 0.4 kg
Manufacturer	Thies

Sensor connection diagram

Sensor	Plug Pin No.	Ammonit Cable Wire Color*	Meteo-40 Digital	Supply Sensor
Wind Direction Data	3	white	IN	
Clock	4	blue	CLK	
Supply	1	red		12 V
Ground	2	black		Main Ground
Heating	5	orange, orange		24 V AC/DC
	6	violet, violet		

Cable type without heating: LiYCY 4 x 0.25 mm²

Cable type with heating wires: LiYCY 8 x 0.25 mm²

Connect the shield logger-sided to Ground (GND)

Wind Vane Compact Potentiometer 2 k Ω

